

Catchpit Chamber 110/160

315mmØ Catchpit 3 x 110mmØ inlet, 1 x 160mmØ outlet

Product Code: SELH03004



Design

Skeletank catchpit chambers are designed to complement Skeletank attenuation and infiltration systems.

Specification

The SELH03004 has a diameter of 315mm and an overall nominal height of 850mm. The polyethylene chamber can be easily reduced on site to suit required invert levels.

Each chamber has 3 number 110mm diameter inlet pipe spigots and 1 number 160mm diameter outlet pipe spigot to suit standard PVC-u push fit drainage pipework.

The SELH03003 chamber has a 50mm deep sump to accommodate the deposition of silt and debris in the collected rainwater for later removal under a regular maintenance regime.

Installation

1. Set out the location of the chamber
2. Excavate to the required depth. Set the chambers on a bed of concrete in accordance with the standard detail drawing. The chambers are supplied with a secondary cover; this cover must be left in place during construction to prevent any debris i.e. Stone, mortar, bricks etc falling into the chamber.

It is recommended that this cover be left in place when the brickwork and final choice of cover & frame has been fixed. Before completion ensure that the secondary cover is not trapped by mortar and can easily be removed.
3. If it is necessary to reduce the height of the chamber, remove the secondary cover, cut the chamber to the required height and replace the secondary cover before installation.
4. Connect the pipe work using standard underground pipes and fittings.
5. Backfill in accordance with the standard detail drawing or specific Contract requirements.
6. To complete the installation, a manhole cover to suit loading requirements should be procured and positioned using brickwork to adjust levels.

Element	Dimensions
Chamber diameter	315mm
Sump depth	50mm
Overall depth	847mm
spigot diameter	3 x 110mm, 1 x 160mm
No. of spigots	4
Material	Polyethylene